

ATTESTATION OF CONFORMITY

Issued to: Xiamen Yankon Energetic Lighting Co., Ltd.
No. 88, Houxiang Road, Haicang District 361026 Xiamen Fujian, China

For the product: Fixed luminaire



Trade name:



Type/Model: WPA2D-N2-M series; WPA2D-N2-V series

Ratings: 220-240 V~; 50/60Hz; 9 / 17 W; 17 / 33 W; 33 / 50 W, Class II; IP66; ta: 50°C (refer to annex model list for detail)

Manufactured by: Xiamen Yankon Energetic Lighting Co., Ltd.
No. 88, Houxiang Road, Haicang District 361026 Xiamen Fujian, China

Requirements: EN IEC 60598-1:2021+A11:2022
EN IEC 60598-2-1:2021
EN 60598-2-24:2013
EN 62493:2015+A1:2022

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6164593.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 17 January 2024

Number: 6164593.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kate Xu
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2



Annex

Document no. : 6164593.01AOC

Model number	Reference model number	Reference model number	Rated voltage	Rated wattage	IP rating
WPA2D-N2-M-1L60 17W	FOB82700v0-ds	COLI-IZC-17-60PD 30N001 COLI-IZC-17-60PD 40N001 COLI-IZC-17-60PD 65N001	220 – 240 V~; 50 / 60 Hz	9 / 17 W	IP66
WPA2D-N2-M-1L120 33W	FOB82800v0-ds	COLI-IZC-33-120PD 30N001 COLI-IZC-33-120PD 40N001 COLI-IZC-33-120PD 65N001		17 / 33 W	IP66
WPA2D-N2-M-1L150 50W	FOB82900v0-ds	COLI-IZC-50-150PD 30N001 COLI-IZC-50-150PD 40N001 COLI-IZC-50-150PD 65N001		33 / 50 W	IP66
WPA2D-N2-V-1L60 17W	FOB82700v1-ds	COLI-IZP-17-60PD 30N001 COLI-IZP-17-60PD 40N001 COLI-IZP-17-60PD 65N001		9 / 17 W	IP66
WPA2D-N2-V-1L120 33W	FOB82800v1-ds	COLI-IZP-33-120PD 30N001 COLI-IZP-33-120PD 40N001 COLI-IZP-33-120PD 65N001		17 / 33 W	IP66
WPA2D-N2-V-1L150 50W	FOB82900v1-ds	COLI-IZP-50-150PD 30N001 COLI-IZP-50-150PD 40N001 COLI-IZP-50-150PD 65N001		33 / 50 W	IP66

Note:

1. "V" means the model have high efficacy, "M" means the model have normal efficacy (120 lm/W).